# Cochlear™ Baha® 5 Power

Cochlear Baha Connect System\* & Cochlear Baha Attract System\*\*





**≰**iPhone | iPad | iPod

needs of patients with mixed hearing loss and single-sided sensorineural deafness (SSD).

Powered by the Ardium™ Smart Wireless platform with SmartSound® iQ signal processing technology and the new BCDrive™ transducer technology, the Baha 5 Power is designed to


Powered by the Ardium™ Smart Wireless platform with SmartSound® iQ signal processing technology and the new BCDrive™ transducer technology, the Baha 5 Power is designed to ensure that your patients will benefit from their best hearing experience across a variety of sound environments. The Baha 5 Power is based on Baha bone conduction technology and designed to work with the Cochlear Baha Attract System, the Cochlear Baha Connect System, the Cochlear Baha Softband and the Cochlear Baha SoundArc™.

The Cochlear™ Baha® 5 Power Sound Processor is a highly advanced bone conduction sound processor from Cochlear. It features sophisticated signal processing and wireless technology. It is a Made for iPhone Hearing Device that supports direct audio streaming from iPhone®, iPad® and iPod touch®. The Baha 5 Power has been developed to meet the

## **Features**

- Fully programmable, power head-worn sound processor with Bluetooth® Smart technology
- Made for iPhone Hearing Device with support for direct audio and data streaming
- 2.4 GHz Wireless technology that connects to Cochlear Wireless Accessories
- BCDrive transducer technology
- 17 channel sound analysis with Wide-band Dynamic Range Compression and Natural Sound Resolution
- 4 user-defined programs with dedicated listening programs for music, outdoor and noisy environments
- Volume rocker to adjust volume settings
- Visual indicator
- Scene Classifier II controlling:
  - Noise Manager II
  - Active Balanced Directionality
  - Active Gain
- Position Compensation II
- Control Sync for bilateral synchronization of program change and streaming
- Dual Track Feedback Manager
- Dedicated fitting rationales for mixed loss, conductive loss and SSD
- Patient optimized fitting with Baha Fitting Software (5.2 or later)
- Wireless fitting with NOAHLink Wireless
- Compatible with FM and digital wireless ALD systems through the Cochlear Wireless Mini Microphone 2+.<sup>†</sup>
- IP63 classified<sup>‡</sup>

## Fitting range



Bone-conduction thresholds ≤ 55 dB HL averaged across 500, 1000, 2000, and 3000 Hz

Air-conduction thresholds may extend into this area

The Baha 5 Power is suitable for individuals with bone conduction thresholds within the yellow area indicated in the fitting range. For further details, see the Candidate Selection Guide.

## Wireless accessories

Cochlear Baha Remote Control 2<sup>§</sup> Order no. 94791 (US)

Cochlear Wireless Mini Microphone 2+†

Mini Microphone 2+ Order no. P770848 (US)

Cochlear Wireless Phone Clip

Order no. 94771 (US)

Cochlear Wireless TV Streamer

Order no. 94761 (US)

## **Apps**

**Baha 5 Smart App**Connects directly to control and monitor the sound processor.

Visit www.Cochlear.com/US for more information.

## Ordering information

The Cochlear Baha 5 Power is delivered in a kit that includes the sound processor, an abutment cover, batteries, a cleaning kit, a tamper-proof tool, a safety line and a document pack. The Baha 5 Power also comes with a small test rod that allows wearers to 'share their Baha experience' with friends and family.

When ordering, specify the language requirement for the document pack (contains important information such as the user manual and warranty card). The sound processor will be delivered with a document pack in the appropriate language.

Baha 5 Power	Order no.
Baha 5 Power Blonde	95470
Baha 5 Power Black	95471
Baha 5 Power Silver	95472
Baha 5 Power Brown	95473
Baha 5 Power Copper	95474
Baha 5 Power Demo	95475

 $<sup>^*</sup>$ The Cochlear Baha Connect System consists of a compatible Baha sound processor, abutment and implant. For details regarding compatibility visit www.cochlear.com/compatibility.

<sup>\*\*</sup>The Cochlear Baha Attract System consists of a compatible Baha sound processor, SP magnet, implant magnet and implant. For details regarding compatibility visit www.cochlear.com/compatibility.

<sup>†</sup> The Baha 5 Power is also compatible with the Cochlear Wireless Mini Microphone 2 (P770844) and the Mini Microphone (94781) (US),  $\ddagger$  IP63 classification excludes battery compartment. The Baha 5 Power is not waterproof. Never wear it in heavy rain, in the bath or shower!


<sup>§</sup> The Baha 5 Power is also compatible with the Cochlear Baha Remote Control (94765)


# Visual indicator Volume rocker Attachment point for the safety line Tamper-proof lock compartment door Program button, Wireless audio streaming button



# Baha Connect System with Baha 5 Power

Measured on skull simulator TU1000.






## Baha Attract System with Baha 5 Power

Measured on Artificial Mastoid IEC 60318-6.





## Technical information (Measurements at full gain)

Frequency Range	250–7000 Hz (ANSI 3.22)	250–7000 Hz (ANSI 3.22)
Peak OFL at 90 dB SPL	123 dB <i>(rel 1 μN)</i>	125 dB <i>(rel 1 μN)</i>
Peak OFL at 60 dB SPL	113 dB ( <i>rel 1 μN</i> )	115 dB <i>(rel 1 μN)</i>
Acousto Mechanical Gain (at 60 dB SPL, 1600 Hz)	49 dB (rel 1 μN /20 μPa)	53 dB (rel 1 μN /20 μPa)
Total Harmonic Distortion (at 60 dB SPL,	Below 3% above 600 Hz	Below 3% above 600 Hz
reference test gain acc. IEC 60118-9)		

Weight, excluding battery	17 g	
Size	36 mm × 22 mm × 13 mm	
Battery Type	675 (Zinc-Air)	
Average Battery Life Time	Typically 80–160 hours*	
Current Consumption	1.2 mA (in silence) 1.4 mA (at 60dB SPL, 1600 Hz)	
Equivalent Input Noise Level	<26 dB SPL	
Processing Delay	4.5 ms	

 $<sup>*\, \</sup>textit{Dependent on streaming, sound environment and gain settings}.$ 

 $For compatibility information {\it visit} {\it www.cochlear.com/compatibility}.$ 

©Cochlear Limited 2020. All rights reserved. Hear now. And always and other trademarks and registered trademarks are the property of Cochlear Limited or Cochlear Bone Anchored Solutions AB. The names of actual companies and products mentioned herein may be the trademarks of their respective owners.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Cochlear is under license.

©2020. Apple, the Apple logo, iPhone, iPad and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.

And roid and Google Play are registered trademarks of Google Inc.

### www.Cochlear.com/US

Cochlear Americas 10350 Park Meadows Drive Lone Tree, CO 80124 USA Telephone: 1 303 790 9010 Support: 1 800 483 3123 Cochlear Canada Inc. 2500-120 Adelaide Street West Toronto, ON M5H 1T1 Canada Support: 1 800 483 3123



